Supplier's name or trade mark:

Beko

Supplier's address :

Arctic S.A Gaesti, Dambovita, 13 Decembrie Street, No 210, Romania

Model identifier:

## WUE7512WPBE 7000440054

Rated capacity (kg) Energy efficiency index (EEI <sub>w</sub> ) Vashing efficiency index Energy consumption in kWh per cycle, based on the eco 40-60 programme at a combination of full and partial loads.	7, 79 1,0	9,5	Dimensions in cm Energy efficiency class	Height Width Depth	84 60
Energy efficiency index (EEI <sub>w</sub> ) Vashing efficiency index Energy consumption in kWh per cycle, based on the eco 40-60 programme at	79	9,5			
Vashing efficiency index Energy consumption in kWh per cycle, based on the eco 40-60 programme at		-	Energy efficiency class	Depth	40
Vashing efficiency index Energy consumption in kWh per cycle, based on the eco 40-60 programme at		-	Energy efficiency class		49
Energy consumption in kWh per cycle, based on the eco 40-60 programme at	1,0	40		D	
ased on the eco 40-60 programme at			Rinsing effectiveness (g/kg)	4,9	
Actual energy consumption will depend on how the appliance is used.	0,685		Water consumption in litre per cycle, based on the eco 40-60 programme at a combination of full and partial loads. Actual water consumption will depend on how the appliance is used and on the hardness of the water.	40	
Maximum temperature inside the treated textile (°C)	Rated capacity	41	Weighted remaining moisture	62,0	
	Half	39	content (%)		
	Quarter	25			
Spin speed (rpm)	Rated capacity	1000		С	
	Half	1000	Spin-drying efficiency class		
	Quarter	1000			
Programme duration (h:min)	Rated capacity	3:27			
	Half 2:41		Туре	Free-Standing	
	Quarter	2:41			
Airborne acoustical noise emissions In the spinning phase (dB(A) re 1 pW)	72		Airborne acoustical noise emission class (spinning phase)	A	
Off-mode (W) (if applicable)	0,50		Standby mode (W) (if applicable)	1,00	
Delay start (W) (if applicable)	4,00		Networked standby (W) (if applicable)	NA	
Ainimum duration of the guarantee offe	ered by the	e supplier :	24 months		
This product has been designed to during the washing cycle	release si	Νο			
Additional information:					